

Desktop Printer


HS 600 DT

Flexible desktop printer HS 600 DT offers high resolution prints up to 4”:

- Ideal compact solution for printing envelopes, magazines, documents etc.
- Easy to expand printheight
- Up to 8 printheads per unit (4”)
- Formats up to 300 mm wide
- The integrated Ucon printer controller offers extended freedom in image design
- Multiple possibilities of working access: Touch PC, Laptop, Monitor/keyboard
- USB connection and networking
- Requires a minimum of skill and training



The HSA Desktop Printer ensures superior quality at high speed utilizing HP TIJ 2.5 technology. The powerful Ucon printer controller is fully integrated into the new compact HSA Mail vacuum transport system.



Technical Details

HS 600 DT

Key features:

- Flexible and expandable
- High speed - linespeed 100 m/min (23.500 C5s /hour)
- Precise transport
- Two controllable vacuum sections
- Left to right travel
- Variable speed
- Easy to service
- Powerful drive with programmable drive unit
- Mounting rails along both edges
- Ethernet interface
- Industrial design

Standard unit:

- V710iJ Streamfeeder
- Transport unit w. bridge and mounts
- Printhead configuration
- Ucon printer controller

Accessories:

- Touch PC, Laptop or Office PC
- Adjustable mounts for monitor or touch PC
- Exit tray
- Misc. topaccessories, bounce rollers, "hold-down" straps etc.
- Floor table or floor cabinet

Technical Data:

Power

230 VAC or 115 VAC

Coatings

Anodised

Environmental conditions

Operating temperature: 10 - 50° C

Humidity (%): 10 - 90 non-condensing

IP rating: 54

CE compliant

Warranty 1 year

Service min. 5 years

Interface:

Ucon controller: USB connector

Printstall: Sub-D 25

Product specifications:

Max. size 305 x 305 mm

Min. size 95 x 95 mm

optional min. 63 x 63 mm

Min/Max thickness: 0,076 - 19,1 mm

Print speed

(horizontal x vertical):

600x600 dpi 38 m/min

600x300 dpi 76 m/min

300x300 dpi 100 m/min

(limited by base)

In software, type in any dpi and max line speed is calculated.

DIMENSIONS: (WxLxH)

Horizontal

working space: 340 x 650 mm

Dimensions: 470 x 1160 x 805 mm

ex. feederunit: 470 x 1160 x 330 mm

Weight: 62 kg

ex. feederunit: 43 kg

Table dim: 1065 x 355 x 760 mm

Weight: 7 kg

Proudly distributed in Australia / New Zealand by Multitec FBM (Asia Pacific) P/L

96 Victoria Rd, Parramatta NSW 2150, Ph: (02) 9890 3225, Fax: (02) 9890 4393

www.fbmaust.com, sales@fbmaust.com.au