

Vacuum Transport Bases

HS 1000/HS 1500

Transport bases for e.g.:

- Ink-jet equipment
- Drying stations
- Labeling equipment
- Off-line or in-line use




HS 1000



HS 1500

Powerful, reliable and precise transport units.

The multi purpose vacuum unit is available in 2 sizes to cover most needs for inkjetting, tabbing, labeling etc.



Technical Details

HS 1000/HS 1500

Key features:

- Use with ink-jet printers, dryers, labelers etc.
- High speed - up to 250 m/min (820 feet/min)
- Optimum encoder reference (precise transport)
- For off-line or in-line printing jobs
- Five controllable vacuum sections (3 in HS1000)
- Left or right travel
- One variable speed and two fixed speeds
- Easy to service
- Powerful drive with programmable inverter
- Can be delivered with heat resistant belts
- 5 belts for accommodating both narrow and wide stock
- Adjustable in height
- Mounting rails along both edges
- Wheels for easy moving of unit
- Adjustable feet for steady placement

Accessories:

- Easy attachable in-feed table w. support
- Sideguides
- Adjustable mounts for monitor, controller etc.
- Bridges for printheads, camera etc.
- Sensor mounts
- Exit tray
- Misc. topaccessories, bounce rollers, "hold down"-straps etc.

Technical Data:

Power

230 VAC / 50Hz or 115 VAC / 60Hz

Motor

2800 Min-1, 0,37 kW

Gear

i=7, n1=400min-1, M=7Nm

Inverter

230V / 0,25kW or 115V / 0,25kW

Safety

Emergency stop (optional external stop)

Coatings

| | |
|----------------|----------|
| Frame | Powder |
| Top base plate | Anodised |

Environmental conditions

Operating temperature: 10 - 50° C
Humidity (%): 10 - 90 non-condensing
IP rating: 54

CE compliant

| | |
|----------|--------------|
| Warranty | 1 year |
| Service | min. 5 years |

DIMENSIONS:

HS1000

| | |
|----------------|--------------------------------|
| Working area: | 495 x 1010 mm |
| Outer dim: | 710 x 1015 x 925 mm (WxLxH) |
| Height adjust: | 895 - 995 mm |
| Weight: | approx. 100 kg |

HS1500

| | |
|----------------|--------------------------------|
| Working area: | 495 x 1510 mm |
| Outer dim: | 710 x 1515 x 925 mm (WxLxH) |
| Height adjust: | 895 - 995 mm |
| Weight: | approx. 125 kg |

Proudly distributed in Australia / New Zealand by Multitec FBM (Asia Pacific) P/L

96 Victoria Rd, Parramatta NSW 2150, Ph: (02) 9890 3225, Fax: (02) 9890 4393

www.fbmaust.com, sales@fbmaust.com.au